



The Mediatrix® 1124 is a high-quality and cost efficient VoIP gateway connecting larger branch offices and multi-tenant buildings to an IP network, while preserving investment in analog telephones and faxes.

It allows Service Providers to deploy rapidly and economically their solutions in medium-size premises and it is the ideal solution for branch office connectivity to larger private networks.

### Key Benefits

#### Voice Functionalities

- Carrier-grade voice quality
- T.38 support
- PSTN bypass option

#### Ease of configuration and management

- Automatic firmware and configuration file download
- SNMP and web management
- TFTP or HTTP auto-provisioning

#### Security

- Support for SNMPv3
- Encrypted configuration files support
- HTTP Digest authentication

#### Network functionalities

- QoS Support
- DHCP client
- Interoperable with equipment from leading industry vendors
- STUN Client

## Mediatrix® 1124 24-port VoIP Access Device



### Mediatrix 1124 Overview

**The Mediatrix 1124 connects up to 24 analog phones and/or faxes to a broadband modem or LAN.**

The Mediatrix 1124 enables cost-effective VoIP deployments in medium-size branch offices and multi-tenant applications.

The Mediatrix 1124 has the additional benefit of supporting high compression codec's simultaneously on each analog voice ports, thus saving valuable bandwidth.

As all other Mediatrix devices, the 1124 provides web interface, giving users a convenient access to the unit for initial set-up. The devices can also auto-provision by fetching their encrypted configuration from a TFTP or HTTP server making installation secure and transparent to the end-users. To further facilitate deployments, factory loaded configurations are possible.

In addition, an optional intelligent PSTN bypass allows Mediatrix 1124 users to make emergency calls and maintain their phone service in the event of a power outage or network failure.

## Functional Description

### FXS Extensions

The Mediatrix 1124 is equipped with Central Office quality SLICs (Subscriber Line Interface Circuit) supporting all the BORSCHT (Battery feed, Overvoltage protection, Ringing, Signaling, Coding, Hybrid, Testing) functions and thus meeting most worldwide telephony standards. Station line length can reach up to 450m in the 2-wire "loop start" signaling arrangement.

The FXS extensions support On-Hook audio transmission, thus providing many advanced CLASS features such as message waiting indication, Caller-ID FSK transmission and such.

The sinusoidal ringing signal frequency can be modified by software. Typical values range from 20 to 50 Hertz, 20 Hertz being the default frequency. Each extension provides its own ring generator and is capable of supplying up to 3 RENs (Ringer Equivalence Number).

Default settings for the FXS extensions are such that BellCore/North American standards are met. On request, port settings may be modified to comply with other known international standards. Software-configurable port setting for international requirements is available.

### Fax Interface

The Mediatrix 1124 can handle G3 fax transmissions at speeds up to 14.4 kbps. Automatic fax mode detection is also available on all extensions, as well as Real-Time Fax-Over IP with T.38 protocol stack. Data handling and synchronization formerly T.4 and T.30 protocols, are processed by the embedded DSP and CPU.

Quality of T.38 fax transmissions is dependent upon the system configuration, type of call control system used, type of Mediatrix units deployed, as well as the model of fax machines used. Should some of these conditions be unsatisfactory, performance of T.38 fax transmissions may vary and be reduced below expectations.

### Analog Modem Interface

The Mediatrix 1124 can be used with analog modems. When configured correctly, modems with high rate capabilities (for instance, V.90) will automatically fall back within the transmission range supported.

Quality of modem transmissions is dependent upon the system configuration, quality of the analog lines, as well as the number of analog-to-digital and digital-to-analog conversions. Modem performance may therefore be reduced below the optimum values stated above.

### Bypass Connection

In addition to the twenty-four extensions, the Mediatrix 1124 has an RJ-11 connector used to connect to a standard PSTN line. During normal operation, this line is *switched out* of the circuit through commuting relay. When power is removed from the Mediatrix 1124, or if the IP network is down, the relay setting is restored to a connected state and the PSTN line can be used as an emergency *Bypass line*. Consequently, a phone/fax used on the first extension will be directly connected to this PSTN Bypass line. The Bypass line can also be triggered with a software control signal. When the error conditions have been cleared or the power is restored, Extension one stays in Bypass connection until the device connected to it is On-Hook. This safety feature ensures that an emergency call does not get disconnected from the PSTN.

### Housing & Power

The Mediatrix 1124 is designed to be rack-mounted on 19 in. industrial racks (EIA-310-D).

AC: Standard power cord receptacle (IEC 320 – C14) for universal AC input internal SMPS

Rear view of the Mediatrix® 1124



Universal Power Supply Unit

## SIP Specific Features

The Mediatrix 1124 supports the SIP signalling protocol as an endpoint entity. It can communicate directly with other endpoints (direct IP call) or register to a SIP call agent should the user request to.

## Full Integration with the *Dial* IPCS Communication Server

When a number is dialed, the Mediatrix 1124 contacts the *Dial* IPCS Communication Server and the server searches through its internal database to translate the dialed number to a corresponding IP address. If there is no match, the server will locate a gateway and place the call on the public switched telephone network (PSTN).

## MGCP/NCS Specific Features

The Mediatrix 1124 uses a Call Agent to provide specific services.

## H.323 Specific Features

The Mediatrix 1124 uses a Gatekeeper to provide specific services.

## Additional Features

### Fully Configurable “PSTN-Like” Experience

The Mediatrix 1124 provides all the familiar tones commonly heard on a standard telephone network. For example, a dial tone is heard as soon as the handset is lifted. Call progress tones such as ringback and busy are also supported.

The Mediatrix 1124 can be configured to accept almost any type of telephone number. For instance, it would be quite simple to configure a network of Mediatrix units to act as a module of a PBX, having its users dial three numbers to reach an extension. It is also very easy to configure the Mediatrix 1124 to behave like the PSTN, for example users can dial “1” and ten numbers when placing a long distance call in North America.

### Remote Configuration / Easy Management

The Mediatrix 1124 can be integrated seamlessly within an existing administrative environment. SNMP support allows device-related adjustment parameters to be modified and polled remotely. Implementation of a web interface provides user-friendly access to common parameters. Firmware upgrade (CPU and DSP code) and configuration files are downloaded via a TFTP or HTTP server. Auto-provisioning of Mediatrix units is performed with added security through configuration file encryption and HTTP digest authentication.

## Industry Standard Protocols

The Mediatrix 1124 has been designed to support all major industry standards used today, as well as those that will eventually be implemented at a later date. Because of this specific design characteristic, the Mediatrix® 1124 can be integrated with existing telephone, fax and LAN/WAN equipment such as bridges, routers and switches.

The following standards are supported:

<b>Vocoders</b>	<ul style="list-style-type: none"> <li>● G.711 (a-law, <math>\mu</math>-law)</li> <li>● G.723.1 (H.323 v4.0)</li> <li>● G.723.1a</li> <li>● G.726 (SIP v5.0, MGCP v5.0)</li> <li>● G.729a (SIP v4.4, H.323 v4.0, MGCP v4.4)</li> <li>● G.729ab</li> </ul>
<b>IP Telephony Protocols</b>	<ul style="list-style-type: none"> <li>● SIP - RFC3261</li> <li>● H.323v3</li> <li>● MGCP</li> <li>● PacketCable™ network-based call signaling (NCS) protocol, PKT-SP-EC-MGCP-I01-990312</li> </ul>
<b>Real-Time Transport Protocols</b>	<ul style="list-style-type: none"> <li>● RTP/RTCP – RFC1889, RFC1890, RFC2833, RFC3389</li> </ul>
<b>Network Management Protocols</b>	<ul style="list-style-type: none"> <li>● SNMPv3</li> <li>● HTTP 1.0 – RFC1945 (SIP v5.0)</li> <li>● Basic and digest HTTP authentication – RFC2617 (SIP v5.0)</li> <li>● DHCP – RFC2131, RFC2132</li> <li>● TFTP – RFC1350, RFC2347, RFC2348, RFC2349</li> <li>● Syslog</li> </ul>
<b>QoS</b>	<ul style="list-style-type: none"> <li>● ToS</li> <li>● DiffServ</li> <li>● 802.1p</li> <li>● 802.1Q</li> </ul>

## General Specifications

### Display

- Power LED
- LAN activity LED
- Ready LED

### Connectors

- 1 RJ-21X TELCO 25 pairs connector, analog phone/fax (FXS) interface
- 1 RJ-11 connector, PSTN bypass
- 1 RJ-45 connector, 10/100 BaseT Ethernet access (autosense: up to 100 Mbps)

### Power

- AC: Standard power cord receptacle (IEC 320 – C14) for universal AC input internal SMPS
- Seamless switch over period if the client UPS detects a power loss and activates within 8 ms.

### Casing / Mechanical

Casing: Plastic ABS UL94 5V  
Installation: rack-mountable, 1U size

### Product Architecture Details

- Supports twenty-four concurrent communications
- DSP-based DTMF detection, generation and synthesis
- DSP-based echo cancellation (G.168)
- DSP-based fax/data relay
- Embedded operating system with 32-bit real-time multitasking Kernel
- Embedded IPv4 TCP/IP stack with configurable QoS implemented by:
  - ToS byte at Network layer 3
  - 802.1p at Data Link layer 2
- Network parameters assigned via DHCP

### Real Time Fax Router Technical Specifications

Automatic selection between voice and fax

<b>Protocols</b>	Group 3 Fax Clear channel (G.711), G.726 or T.38 Real Time Fax Over IP protocol Stack
<b>Fax Data Compression</b>	MH
<b>Fax Transmission Protocols</b>	Up to 14.4 kbps

### Analog Line Interface (FXS)

- RJ21X connector
- DC feeding of the access line protected for over voltage
- Loop current detection and hook flash detection capable
- Generation of Selective Ring

<b>Trunk Type</b>	Loop Start: capable of Wink and Immediate signalization
<b>Ring Source</b>	45 VRMS max @ 20 up to 50 Hz (selectable) sine signal
<b>Nominal Impedance</b>	BellCore compliant 600/900 ohms default setting. Impedance Software Configurable.
<b>Ring Drive Capacity</b>	Up to 3 ringer equivalents (3 RENs) per extension
<b>Loop Current Range</b>	15 to 32 mA factory set. Default 20 mA regulated
<b>Ring Trip Detection Time</b>	2 ring cycles max
<b>On-Hook Voltage</b>	-48 VDC
<b>Freq. Response</b>	200 Hz to 3400 Hz $\pm$ 2 dB (Tx/Rx)
<b>Return Loss</b>	500-3200 Hz: 30 dB

### Miscellaneous Audio Specifications

- Software input and output level adjustable within the range -36 dB to +12 dB.
- Software-adjustable dynamic and static jitter buffer protection.
- Programmable by country: Call progress tone generation including dial tone, busy tone, ringback and error tones.
- DSP-based echo control device.
- Silence detection/suppression level software adjustable.

### DTMF Tone Detection

<b>16 Digit DTMF Decoding</b>	0 to 9, *, #, A, B, C, D
<b>Permitted Amplitude Tilt</b>	High frequency can be +4 dB to -8 dB relative to low frequency
<b>Dynamic Range</b>	-25 dBm to 0 dBm per tone
<b>Frequency Accept</b>	$\pm$ 1.5% of nominal frequencies
<b>Minimum Tone Duration</b>	40 ms, can be increased with software configuration
<b>Interdigit Timing</b>	Detects like digits with a 40 ms interdigit delay

## DTMF Tone Generation

Per Frequency Nominal	-8 dBm to -5 dBm
Frequency Deviation	Within 1.5% of nominal values

## Standards Compliance

Agency Approvals	<ul style="list-style-type: none"> <li>● UL</li> <li>● CE Marking</li> <li>● FCC</li> <li>● Anatel</li> <li>● NOM</li> </ul>
Safety Standards	<ul style="list-style-type: none"> <li>● UL60950 3rd Edition (2000)</li> <li>● CAN/CSA-C22.2 No. 60950-00</li> <li>● IEC 60950 1st Edition (2001), with all national deviations</li> <li>● Anatel Resolution 238:2000</li> <li>● NOM-019-SCFI-1998</li> </ul>
Emissions	<ul style="list-style-type: none"> <li>● FCC Part 15 (1998) Class B</li> <li>● EN55022 (1994) Class B, with amendments A1 and A2</li> <li>● EN61000-3-2 (1995) Harmonic Current Emissions</li> <li>● EN61000-3-3 (1995) Voltage Fluctuations and Flicker</li> <li>● Anatel Resolution 237:2000</li> </ul>
Immunity	<ul style="list-style-type: none"> <li>● EN55024 (1998) and A1 (2001) including the following:               <ul style="list-style-type: none"> <li>● EN61000-4-2 (1995), ESD</li> <li>● EN61000-4-3 (1996), Radiated RF</li> <li>● EN61000-4-4 (1995), Burst Transients</li> <li>● EN61000-4-5 (1995), Surge</li> <li>● EN61000-4-6 (1996), Conducted RF</li> <li>● EN61000-4-11 (1995), Voltage Dips and Interruptions</li> </ul> </li> </ul>
Telecom	<ul style="list-style-type: none"> <li>● FCC Part 68:Subpart D</li> <li>● Industry Canada CS-03 Issue 8, Part 1</li> <li>● TBR21:January 1998</li> </ul>

## MTBF Value (preliminary evaluation)

The estimated Mean Time Before Failure (MTBF) value of the Mediatrix 1124 is 180 000 hours at 25 degrees Celsius ambient temperature. It has been defined using RelCalc v5.0, Bellcore method (LimitedStress - Method I, Case 3) with 4 extensions ringing, 20 on standby.

## Power Consumption

Idle Mode: 120Vac	0.35A 23W
Idle Mode: 240Vac	0.18A 25W
24 Extensions Off-Hook (worst case): 120Vac	1.2A 70W
24 Extensions Off-Hook (worst case): 240Vac	0.6A 65W

## Operating Environment

Operating Temperature	0°C to 40°C
Humidity	Up to 85 %, non-condensing
Storage	-20°C to +70°C

## Dimensions and Weight

Height	4.4 cm (1.74 in.) approx.
Width	43 cm (17.19 in.) approx.
Depth	21 cm (8.4 in.) approx.
Weight	1.7 kg (3.7 lbs)

## Warranty

All products carry Mediatrix Telecom's standard one-year hardware and software warranty. An extended warranty is available.

© 2005 Proprietary information of Mediatrix Telecom, Inc. All rights reserved. Do not copy without the written consent of Mediatrix Telecom, Inc. Mediatrix and the Mediatrix logo are registered trademarks of Mediatrix Telecom, Inc. All other trademarks are held by their respective owners.

The specifications and information regarding this product are subject to change without notice. Every effort is made to ensure the accuracy of this document. However, due to ongoing product improvements and revisions, Mediatrix Telecom, Inc. cannot guarantee its accuracy, nor can it accept responsibility for errors or omissions.

